



Mobile Device USB Micro-B to HDMI Display SlimPort Adapter Cable

- Allows a mobile device to be connected to an HDTV or Projector
- Supports up to 1080p resolutions
- SlimPort technology allows content to be displayed while the mobile device is charged
- Lifetime Warranty

*Note: The smartphone, tablet or other mobile device being used with the adapter must support SlimPort technology.

Specifications: Mobile Device USB Micro-B to HDMI Display SlimPort Adapter Cable

Electrical Characteristics:

Resolution Supported:	1080p
Max. Conductor DC Resistance:	32AWG;588Max
Impedance:	1005
Intra-pair skew:	15ps/m max
Voltage Rating:	30V

Physical Characteristics:

Minimum Bend Radius:	12mm
Operating Temperature:	0°C to 70°C
Storage Temperature:	-10°C to 40°C
Approvals:	CE
Warranty:	Lifetime

Conductor (3):

Conductor:	34AWG (7/0.06 TC)
Insulation:	HD-PE ID: $\phi 0.63 \pm 0.05$
Shield:	AL Mylar Wrap SP(38 ± 2)/0.127T
Drain:	32AWG (7/0.8TC)

Conductor (1):

Conductor:	28AWG (7/0.127 TC)
------------	--------------------

Connector:


Connector Type:	USB Micro-B
Gender:	Male
Contacts:	Gold Plated 1 μ
Hood:	Molded PVC

Connector:

Connector Type:	HDMI A
Gender:	Female
Contacts:	Gold Plated 1 μ
Hood:	Molded PVC

Overall Cable

Jacket:	PVC
OD:	3.5 ± 0.15



Specifications: Mobile Device USB Micro-B to HDMI Display SlimPort Adapter Cable

Part Number	Description	Weight (Kg)
80934	Mobile Device USB Micro-B to HDMI Display SlimPort Adapter Cable	0.025

